




The project is supported by the Europe's Rail and its members. Funded by the European Union. Views and opinions expressed are however those of the author(s) only and do not necessarily reflect those of the European Union or Europe's Rail Joint Undertaking. Neither the European Union nor the granting authority can be held responsible for them.



Co-funded by
the European Union



AR Tool



05 February 2026

Workflow Overview

1st Loop

1. Inspection

- Scanning
- Data processing (Digital Twin + decision layer)

2. Maintenance

- AR Visualisation of corrective actions (Modes: Welding + Grinding + Combined)
- 3D Printed Profile Guides (Modes: Welding)

2nd Loop

1. Re-scan and Update data

2. AR verification & threshold mode (Modes: Welding + Grinding + Combined + Threshold)

Goal:

- ✓ Reduce inspection time,
- ✓ Improve inspection records,
- ✓ Support W/G decision-making,
- ✓ Improve repair QC

Intervention Loop

MONITORING



INSPECTION

- 3D scanning
- Data Processing




MAINTENANCE

- AR Visualisation
- 3D templates



1. INSPECTION: AR alignment

- QR codes placed on the railway crossing during inspection
- QR codes remain in place for maintenance and quality control
- iPad uses QR codes to spatially align AR content
- ✓ AR aligns pre-processed inspection results



1. Inspection: 3D Scanning

- High-Fidelity 3D Data Capture
- Fast operation
- Works in day and night
- Captures full crossing geometry with sub-mm accuracy
- Real-time 3D reconstruction in the device
- Portable & field-ready (battery powered)
- Create highly detailed inspection reports/database

Used for either:

- ✓ Inspection
- ✓ To inform welding/grinding
- ✓ Quality control after welding/grinding



1. INSPECTION: Data Processing

What is Digital Twin?

Digital representation of a real railway crossing, continuously updated using 3D scan data, to support prediction, decision-making, and maintenance guidance.

In XCROSS, the Digital Twin enables:


- ✓ Understanding wear and degradation
- ✓ Computing an achievable target profile
- ✓ Generating actionable repair guidance (AR + 3D templates)



1. INSPECTION: Data Processing

Why do we need Digital Twin?

- 3D scanning captures the current worn geometry (what the crossing looks like today)
- Maintenance requires a target repair profile (what the crossing should look like after intervention).
- Geometry alone does not indicate:
 - where material should be added (welding)
 - where material should be removed (grinding)
 - whether the repair improves long-term performance
- **A Digital Twin links inspection data to engineering outcomes**, enabling: consistent, traceable, and optimised intervention planning





1. INSPECTION: Data Processing


Why do crossings degrade?

- Crossings experience high-impact forces
- Wear evolves over time
- Geometry changes affect safety and ride quality

Distance= 22.373m, time= 0.00s, v=140km/h





2. INSPECTION: Examples of Turnout Defects Observed on Field




No.	Defect type	Required action
1	Gauge corner wear	Grinding
2	Running band deformation /plastic flow	Grinding + monitoring
3	Surface spalling/flaking	Light grinding + monitor for crack propagation
4	Head wear/abrasion	Grinding or weld restoration (depending on depth)
5	Crossing nose material loss	Weld or component replacement

1. INSPECTION: Data Processing



Corrections for alignment and irregularities






Circular interpolation for high-fidelity modeling

1. INSPECTION: Data Processing

Scanned Crossing Geometry



UoL Crossing @ University of Leeds



1. INSPECTION: Data Processing

High- VS Low-Fidelity Modelling

Balancing speed and accuracy:




Model type	Purpose in XCROSS	Characteristics
Low-fidelity	Rapid approximation of scanned geometry	Fast, smooth, suitable for optimisation
High-fidelity	Accurate representation for wheel-rail dynamics	Captures critical contact zones and impact behaviour

Together, they ensure the target geometry is both achievable and safe

1. INSPECTION: Data Processing

High-Fidelity Modelling of Railway Crossings

Scanned Versus Approximated B-Spline Crossing Profiles



Weighted B-Spline Approximation:


Close to the actual scanned geometry obtained from 3D scanner (Particular emphasis on top of nose and wing rail)

1. INSPECTION: Data Processing


High-Fidelity Modelling of Railway Crossings in VI-Rail

- Full 3D multibody vehicle-track interaction modelling with wheel-rail contact mechanics.
- Explicit modelling of crossing geometry (frog and wing rails)
- Accurate simulation of impact forces and transient dynamics at crossings

Validation: Measured UoL crossing versus Approximated B-spline rail profiles




Validation: Measured UoL crossing versus Approximated B-spline rail profiles




1. INSPECTION: Data Processing

Output: Overlay generation



weld/grind zones identified


Intervention required



DT converts scanned crossing geometry into an achievable target profile, which is then used to generate the intervention zones visualised in AR.

2. MAINTENANCE: What is Augmented Reality?

- Technology that overlays digital information onto the real world
- Enhances what users see and interact with
- Can display images, measurements, instructions, or visual cues
- Provides guidance, context, and actionable insights in real time
- Supports faster, more accurate decision-making





2. MAINTENANCE: On-Site Visual Guidance Augmented Reality App

- Displays the target profile superimposed onto the real crossing
 - Colour-coded overlays. E.g.
 - Blue → grinding required
 - Yellow → welding required
 - Anchors to the real geometry using scan alignment QRs
-
- ✓ Engineers see exactly **where** and **how much** to grind or weld
 - ✓ Repeat scanning + AR in a loop for quality control
 - ✓ Record work quality






2. MAINTENANCE:

- 1. Vertical wear/material loss → weld build-up required
- 2. Minor Material excess → grinding required




2. MAINTENANCE: AR Maintenance Modes

Mode	Purpose	Stage
Welding	Material addition	Maintenance/Quality Control
Grinding	Material removal	Maintenance/Quality Control
Combined	Mixed defects	Maintenance/Quality Control
Threshold/QC	Pass–fail verification	Quality control



Mode-based visualisation reduces cognitive load for engineers

2. MAINTENANCE: AR Quality Control (QC) / Threshold Mode





Mode	Purpose	Stage
Welding	Material addition	Maintenance/Quality Control
Grinding	Material removal	Maintenance/Quality Control
Combined	Mixed defects	Maintenance/Quality Control
Threshold/QC	Pass–fail verification	Quality control



- ✓ Areas requiring further cutting or material addition
- ✓ “OK” zones within tolerance
- ✓ Pass/fail visualisation directly on the crossing
- ✓ Visual Aids included

2. MAINTENANCE: Colour Mapping and Accessibility

- AR overlay visualised using colour-coded heat maps
- Multiple colour maps are supported
- Colour scales can be selected to suit user preference and viewing conditions
- Designed to support users with **different colour vision abilities**



2. MAINTENANCE: Additional Colour Options




Note: Synthetic heatmap for demonstration only

2. MAINTENANCE: AR Visualisation Control & Transparency

Transparency control

- Transparency is adjusted using a **user-controlled slider bar**
- Allows real-time adaptation to lighting and surface conditions
- Supports safe and clear visibility of the real crossing



Note: Synthetic heatmap for demonstration only




2. MAINTENANCE: AR Visualisation Control & Transparency Modes

1. Uniform transparency

- Homogeneous transparency across the entire overlay
- Used to maintain visibility of the real rail surface
- Transparency level adjustable by the user

2. Discrete (priority-based) transparency

- Higher colour intensity in areas requiring maintenance
- Reduced visibility in non-critical regions
- Transparency remains adjustable but applied selectively



2. MAINTENANCE: Field usability for railway maintenance

- Tablet-based AR system
- Hands-free operation using an adjustable mounting arm
- Fast QR-based setup on-site
- Designed for outdoor railway environments
- Clear visual filtering via AR modes



STAKEHOLDER ENGAGEMENT: Feedback → Improvements → Impact

1. QR codes

- Stay in place from inspection through maintenance, keeping AR accurately aligned.
- Must be durable (weather-, heat-, and dust-resistant) to survive on-site grinding and welding.

2. AR App

- Simplified overlays with clear grind vs weld regions (colour-blind-safe).
- Expert-reviewed scenarios (grind/weld/combined/thresholds).
- On-device prompts highlight intervention areas and tolerance/pass–fail limits.

3. Integrated Workflow

- ✓ Scan → AR → re-scan loop ensures accurate, consistent, and repeatable repairs.

